

Article  
19

10/523977

DT05 Rec'd PCT/PTO 08 FEB 2005

SPF083US

After amendment of claims under Article 19 (1)

# CLAIMS

1. A refrigerator unit characterized by comprising:

means, which is provided between a power source and a

5 motor for driving an intake/exhaust valve managing an  
intake/exhaust cycle time of a refrigerator unit, for varying  
a frequency of the motor for driving the intake/exhaust valve;

a temperature sensor for detecting a temperature of a  
thermal load unit of the refrigerator unit; and

10 a controller for controlling the means for varying the  
frequency of the motor for driving the intake/exhaust valve in  
accordance with an output signal of the temperature sensor.

2. A cryopump characterized by comprising the  
refrigerator unit according to claim 1.

15 3. A cryogenic refrigerator characterized by using a  
compressor unit comprising:

means, which is provided between a power source and a  
compressor main body motor of the compressor unit, for varying  
a frequency of the compressor main body motor;

20 a high pressure sensor attached to a high pressure  
refrigerant pipe connecting an outlet of the compressor main  
body with a refrigerant supply port of the refrigerator unit;

a low pressure sensor attached to a low pressure  
refrigerant pipe connecting an inlet of the compressor main  
25 body with a refrigerant discharge outlet of the refrigerator

Article  
19

unit;

a controller for controlling the means for varying the frequency of the compressor main body motor in accordance with output signals of the high pressure sensor and the low

5 pressure sensor, and

characterized in that a plurality of the refrigerator units according to claim 1 and one or more of the compressor units constitute the cryogenic refrigerator.

4. A cryogenic refrigerator characterized by using a  
10 compressor unit comprising:

means, which is provided between a power source and a compressor main body motor of the compressor unit, for varying a frequency of the compressor main body motor;

a differential pressure sensor provided between a high  
15 pressure refrigerant pipe connecting an outlet of the compressor main body with a refrigerant supply port of the refrigerator unit and a low pressure refrigerant pipe connecting an inlet of the compressor main body with a refrigerant discharge outlet of the refrigerator unit;

20 a controller for controlling the means for varying the frequency of the compressor main body motor in accordance with an output signal of the differential pressure sensor, and

characterized in that a plurality of the refrigerator units according to claim 1 and one or more of the compressor  
25 units constitute the cryogenic refrigerator.

Article 19  
5. A cryopump characterized by comprising the cryogenic refrigerator according to claim 23 or 34.

6. The cryopump according to claim 5, comprising:

a temperature sensor for detecting a temperature at any optional position of a cryopanel of the cryopump; and  
a controller for controlling the means for varying the frequency of the motor driving the intake/exhaust valve managing the intake/exhaust cycle time of the refrigerator unit in accordance with an output of the temperature sensor.

7. A superconductive magnet characterized by comprising the refrigerator unit according to claim 1.

8. A super conductive magnet characterized by comprising the cryogenic refrigerator according to claim 23 or 34.

9. The superconductive magnet according to claim 7 or 8, comprising:

a temperature sensor for detecting a temperature of any optional position of the superconductive magnet; and

a controller for controlling the means for varying the frequency of the motor driving the intake/exhaust valve managing the intake/exhaust cycle time of the refrigerator unit in accordance with an output of the temperature sensor.

10. A cryogenic measuring apparatus characterized by comprising the refrigerator unit according to claim 1.

11. A cryogenic measuring apparatus characterized by comprising the cryogenic refrigerator according to claim 23 or

Article  
19

34.

12. The cryogenic measuring apparatus according to claim 10 or 11, characterized by comprising

a temperature sensor for detecting a temperature of any optional position of the cryogenic measuring apparatus; and a controller for controlling the means for varying the frequency of the motor driving the intake/exhaust valve managing the intake/exhaust cycle time of the refrigerator unit in accordance with an output of the temperature sensor.

13. A simple liquefaction apparatus characterized by comprising the refrigerator unit according to claim 1.

14. A simple liquefaction apparatus characterized by comprising the cryogenic refrigerator according to claim 23 or 34.

15. The simple liquefaction apparatus according to claim 13 or 14, comprising:

a temperature sensor for detecting a temperature of any optional position of the simple liquefaction apparatus; and

a controller for controlling the means for varying the frequency of the motor driving the intake/exhaust valve managing the intake/exhaust cycle time of the refrigerator unit in accordance with an output of the temperature sensor

16. The simple liquefaction apparatus according to claim 13 or 14, comprising:

liquid-level detecting means within a liquid storage

Article  
19

container of the simple liquefaction apparatus; and

a controller for controlling means for varying a  
frequency of a motor driving an intake/exhaust valve managing  
a intake/exhaust cycle time of a refrigerator unit in

5 accordance with an output of the liquid-level detecting means.